#### **NISTIR 6527**

# Measurement Needs for Fire Safety: Proceedings of an International Workshop

Thomas J. Ohlemiller Erik L. Johnsson Richard G. Gann



### Measurement Needs for Fire Safety: Proceedings of an International Workshop

Thomas J. Ohlemiller
Erik L. Johnsson
Richard G. Gann
Building and Fire Research Laboratory
National Institute of Standards and Technology
Gaithersburg, MD 20899-8653

June 2000



U.S. Department of Commerce William M. Daley, Secretary

Technology Administration
Dr. Cheryl L. Shavers, Under Secretary of
Commerce for Technology

National Institute of Standards and Technology Raymond G. Kammer. Director

#### NOTICES:

Works of authors who are not staff members of NIST are provided for information purposes.

NIST is not responsible for their content.

The identification of any commercial product or trade name does not imply endorsement or recommendation by the National Institute of Standards and Technology, nor is it intended to imply that the product identified is necessarily the best available for the purpose.

as day

### Experimental Data for CFD Models

Dr. George Hadjisophocleous, P.Eng.

National Research Council Institute for Research in Construction Fire Risk Management Program


#### **Outline**

- Introduction
- CFD model description
- Input data needed
- Data for model validation
- Summary

JAC CARC

















#### Computation vs Experiment


- "The only one who believes the numerical results is the author"
- "Everyone believes the experimental results except the experimentalist"

isig-chig

#### **CFD** Models

- Divide space into very small control volumes
- Solve the fundamental equations for mass, momentum energy and species concentration for each control volume

THE CHIE



#### **CFD Model Inputs**

- · Geometry of space/compartment
- · Openings, obstacles
- · Grid distribution
- · Solution variables
- · Boundary conditions
- · Fire representation

**ナカロ・ひかり** 

#### Input data - Geometry

- · Compartment dimensions
- Partitions
- Obstacles
- Openings

inc con

#### Input Data - Initial Conditions

- Temperature distribution in solution domain
- · Air movements
  - Heat sources
  - Openings, wind effects
  - Stack effect

1350・57316

#### Input Data - Boundary Conditions

- Velocity
  - openings
  - leakage areas
  - surface roughness
- Energy
- Thermal properties of boundaries
- radiative properties
- Dynamic changes to boundary conditions
  - Doors windows open during test
  - fire size changes during test
  - forced ventilation activates during test

1710 - CHILD

#### Input data - Fire

- · Heat release rate vs time
- Yield fractions for CO, CO<sub>2</sub>, and other toxic gases
  - representative of fuel and scenarios considered
  - yield data usually from bench tests
- · Ideal if productions are per unit mass
- · Location of fire
  - area
  - height
  - plume characteristics

לובוט לובנ

#### **Combustion modelling**

- Type of fuel, thermal, thermodynamic and combustion properties
- Rate of release of fuel into domain
- inpu
- calculated very difficult for furniture

HID-CHAC

#### Input data - Detection Systems

- Location
- Characteristics

  - RTI rate of temperature rise

SING-CHILD

#### Input data - Mechanical Ventilation

- · Location and area of inlets/outlets
- · Flow rates
- · Properties ambient air
- · Time of activation

がじしいがじ

### **CFD Model Results** ING-GING

#### **Direct Output Data**

- Temperatures
- Velocities
- · Concentration of toxic gases
- Radiation fluxes
  - Not economical to get adequate data especially for large compartments


物で・公司な

#### Indirect Output Data

- Fire heat release rates
- · Upper layer properties: temperature, CO, CO<sub>2</sub>
- · Upper layer height
- · Plume entrainment rates
- · Flows through openings

ココケージコリ

# One to One Comparisons THE CASE



#### Needed for CFD Models

- Compartment characteristics
- · Initial conditions
- Dynamic conditions
- Fire characteristics
- $\bullet$  Temperature, CO,  $\mathrm{CO}_2$  distributions vs time
- Flow rates

FIFE-CENT